AUTOMATION, AMS SMT & LEAN MANUFACTURING

Cleaning Process

1 STEP BOT. di.water

2 STEP **TOP** di.water

3 STEP BOT. **AIR**

4 STEP **TOP** AIR

5 STEP BOT. **AIR**

Features of Nozzle Cleaner

The effect of Carbon reduction by using distilled water

Possible to clean 12 nozzles at the same time

Easy to operate with touch panel

Reduce the time to change the nozzle by using the nozzle holder

Pick up rate improvement

Mounting efficiency improvement

Quality improvement

Labor-saving effect

Nozzle Cleaner BSE BOSUNG ENG Co., Ltd. **ENC-12**

▶ Patent Pending

ECO

NOZZLE

ENC-12

CLEANER

Specifications

Nozzle Head		12 Head
Compressed air	Туре	Clean air
	Pressure	7kg/cm²
Cleaning water	Туре	Distilled water
	Tank capacity	4000cc (Max 4500cc)
Input power supply	Voltage	DC100~250V(Free Voltage)
	Plug	3-pin (with ground) plug
	Cable length	1.6mm or more
	Power consumption	200W
	Weight	about 43kg

NOZZLOSCOPE

► Nozzle Inspention System



Result of Washing Nozzle

Maker	Before	After
НІТАСНІ		eaning for ninutes
ҮАМАНА		eaning for ninutes
Panasonic		eaning for ninutes